



# SOLID 105A3-2

## Ideal for:

- > Just-in-time applications
- > On-demand printing
- > Business and workflow documents  
Month end invoice runs

## HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- > Minimal downtime and extremely long maintenance intervals
- > Toner refill possible during operation
- > Extremely fast printing speed
- > Flexible expansion options for paper feed and tray
- > Duplex printing at full printing speed
- > Optional IPDS emulation making it the printer of choice for IBM solutions

## HIGHEST PERFORMANCE FOR BUSINESS, LOGISTICS AND PRODUCTION



## SOLID 105A3-2

When highest printing performance really matters, the SOLID 105A3-2 is the perfect choice: the scorching printing speed of up to 105 A4-pages a minute and extremely long maintenance intervals predestine this model for deployment in print-intensive business and logistics applications. Face-up output as well as SPS control and Status Out options ensure the optimal prerequisites for integration in production lines. The SOLID 105A3-2 combines highest levels of reliability with versatile paper handling capabilities.

## Print Engine

<b>Print technology</b>	Laser, OPC heat / pressure
<b>Controller</b>	MPC 3.6
<b>Print speed</b>	up to 105pages/minute (A4) up to 52 pages/minute (A3)
<b>Print resolution</b>	max. 600 dpi x 600 dpi
<b>Duty cycle</b>	up to 400.000 pages (A4 landscape) (based on a using period of 60 months) max. 500.000 pages (A4 landscape)
<b>Power supply</b>	220-240 V/50 Hz
<b>Power consumption</b>	13A
<b>Dimensions (WxDxH in mm)</b>	870 x 760 x 980 (printer only) 1080 x 810 x 1190 mm (incl. Display)
<b>Weight</b>	ca. 300 kg (without options)
<b>Environment temperature</b>	10 - 30°C
<b>Relative humidity</b>	20 - 85 % (rel., non condensing)
<b>Interfaces</b>	USB IEEE 1284 (Centronics) Ethernet-Interface 10/100/1000 MBit, bi-directional (TCP/IP)
<b>Memory</b>	RAM: 2GB Flash: 50MB

## MPC 3.6 High-End Print-Controller

### Emulations

MICROPLEX IDOL, HP-PCL5/ HPGL, AGFA Reno,  $\mu$ -Postscript, LN03+, BULL-MP6090, Etimark MP-1220, TEC Bx72, TEC B6xx, Diablo 630, IBM Proprinter, EPSON FX-80 (ESC/P), MT-600/MT40, IDS, ANSI Genicom, TIFF, XML (SAP® RFID), CUPS Raster, RFM

### Optional Emulations

CODE-V (Magnum), XEROX XES, KODESCRIPT+, Prescribe/PSB 2, IGP-10, IGP/PGL, Datamax, Labelpoint, LDC, ZPLII, EPL 2, Intermec Direct Protocol, IER Command, cab, Godex EZPL, Barcode 2, HP Designjet, IPDS, AEA, AFP, Status-Out, PDF, TN3270 (Telnet terminal emulation) (more emulations on request)

### Barcodes

Codebar, Code39, MSI, PDF417, Interleaved 2/5, Interleaved 2/5 (3-Stroke Datalogic), Interleaved 2/5 (3-Stroke Matrix), EAN-8, 13, 128, Add-On-Codes, Code11, Code93, Code 128, UPC-A, UPC-E

### Optional Barcodes

Datamatrix, Maxi-Code, QR Code, Aztec-Code, USD-5 (more barcodes on request)

### Additional functions

<b>Network capabilities</b>	authentication standard IEEE 802.1x
<b>Intelligent barcode generation</b>	on-the-fly in the printer
<b>Format splitting</b>	in several subformats by command
<b>Integrated form management</b>	up to 12 MB flash for forms and fonts inside the printer

### Optional functions

#### Status-out

gives notice of each correctly printed page via interface. Further features can be found in the manual.

#### Programmable GPIO-Interface (SPS-Control)

EMBEDDED INTELLIGENCE – Enabling two-way communication between printer and a PLC.


Integration of the printer into production lines is possible, controlled by GPIO-interface

Customer / Application specific modifications possible.



## Printable Media

<b>Size</b>	A5R* - A3W*
<b>Weight</b>	60 to 220 g/m <sup>2</sup> max. 300 g/m <sup>2</sup> (option 3430 is required)



## Paper Path

### Input

1+2: 1.200 and 800 sheets (A4/Letter)  
cassette 3: 500 sheets (B5R\* bis A3W\*\*)  
cassette 4: 500 sheets (A5R\* to A3W\*\*)

### Optional

up to 3.500 sheets A4, B5 (3433)  
up to 5.000 sheets (3430, each 2.500 sheets in tray 5 and 6)  
A3W\*\* - A5R\* (no offset)

### Output

faceup / face down

### Optional

finisher saddle stitching (Art. 3440)  
4000 sheets, 100-sheets-stitching  
A3 - B5R\* (offset/stitching), A3W\*\* - A5R  
(no offset) (more options on request)

\* R = short side feeding

\*\*A3W = 12" x 18" (304mm x 457mm)

The brand names referred to are the registered trademarks of the respective companies. All figures and details in italics and highlighted in color are optional. Technical data is subject to change. The information contained in this specification sheet refers exclusively to the described details and not to warranted characteristics. No guarantee is assumed. The information do not exempt from the obligation for inspection of each respective individual case. Version 16.02.2021



**Microplex Printware AG**  
Panzerstraße 5 | 26316 Varel | Germany  
phone +49 4451 91 37-0 | fax +49 4451 91 37-49

